

## DECLARATION OF PERFORMANCE

No. 001/2025

1. Unique identification code of the product-type:

**A47401 UNI CARPORT, Pre-fabricated structural steel carport – hot-dip galvanized S355JR, powder coated, Execution Class EXC2**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**A47401**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Free-standing steel structure (carport) for outdoor use – permanent construction in accordance with EN 1991 (loads), EN 1993 (steel design)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Unipromet DOO, Bulevar oslobođenja Čačka 92a, 32103 Konjevići, Čačak, Srbija**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in REGULATION (EU) No 305/2011, Annex V, EU 568/2014

**System 2+**

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified factory production control certification body – TÜV SÜD Czech, identification No. 1017 – performed initial inspection of the manufacturing plant and factory production control and continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control No. 1017-CPR-11.406.794 Rev. 2**

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Tolerances on dimension and shape	Class 1	EN 1090-1:2009+A1:2011
Weldability	EN 10025-2 – S355JR,	EN 1090-1:2009+A1:2011
Impact strength	27 J (20 °C,)	EN 1090-1:2009+A1:2011
Reaction to fire	Uncoated and hot-dipped galvanized components: Material classified – Class A1 Coated components: classification according to EN 13501-1	EN 1090-1:2009+A1:2011
Release of cadmium and its compounds	NPD	EN 1090-1:2009+A1:2011
Emission of radioactivity	NPD	EN 1090-1:2009+A1:2011
Durability	Coated components: surface prepared according to EN 1090-2. Protective paint systems in accordance with EN ISO 12944-5	EN 1090-1:2009+A1:2011
Load bearing capacity	According to design	EN 1090-1:2009+A1:2011
Deformation in the serviceability limit state serviceability	According to design	EN 1090-1:2009+A1:2011
Fatigue strength	According to design	EN 1090-1:2009+A1:2011
Resistance to fire	see reference: Design for gallery walk development on the 1573-0-0-24	EN 1090-1:2009+A1:2011
Manufacturing:	According to specification A47401 to EN 1090-2, EXC2	EN 1090-1:2009+A1:2011

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Dorđe Joksić, Quality Assurance director**

(name and function)

Čačak / 30.5.2025

(place and date of issue)

